

LED-Pendant Light 4

Model A-6 HPower LED

The LED pendant lamp 4 is a faithful reconstruction of the A-6 model. Due to its rotationally symmetrical light distribution, this lamp is ideally suited for the illumination of squares, streets, residential areas, green spaces and driveways. The luminaire is equipped with energy-efficient innovative LED technology. Choose between golden-yellow lighting that makes the surroundings appear lively and natural, or very bright safety lighting with convincing light quality.

Materials:

Luminaire housing: Made of weatherproof natural aluminum
Hinges and locking parts: Stainless steel or galvanized sheet steel
Other luminaire components: Galvanized or hot-galvanized steel
Reflector: Powder-coated to RAL 9016
Glass dome: Borosilicate glass; design: closed

On request and at an extra charge, paint finishes according to the RAL color table and FerroGrip special coating are available.

Technical description:

Distribution chamber: 4
Mounting interface: G1/2 inch external thread
Accessories: Ball joint G1/2 inch x G1/2 inch

PlugBox: on/off: Switching function on/off

PlugBox ESS Basic: Adjustability of the basic brightness

PlugBox ESS Light: Adjustability of the basic brightness | Adjustability of the reduction brightness

Half-night switching via control voltage 230V AC

MaxiDimm3000: For dimming and/or partial switch-off for balanced and unbalanced Lighting Solutions

Switching input: 230V AC | Interface: 1-10V



Main dimensions:
Height: 632 mm
Width: 382 mm
Weight: 7 kg

His.lux® LED-Modul Serie 333



TECHNICAL DATA

System power	6 - 36 Watt
Expected life	>60.000 Std.
Color temperature	2700K*
Luminous flux	2225 lm (36 Watt)
Color rendering	CRI > 85
IP protection class	IP 65
Historical diffuser	PC satined
Application area	-40°C bis +55°C
Protection class	I oder II

*Color temperature freely selectable

NewNight® CONE LED-Modul



TECHNICAL DATA

System power	8 - 25 watts
Expected life	>60.000 H.
Color temperature	4100K*
Luminous flux	2620 lm
Color rendering	CRI > 85
IP protection class	IP 65
LED cover	PC transparent or satined
Application area	-40°C bis +55°C
Protection class	I oder II

*Color temperature freely selectable

Due to the complexity of the many possible combinations of drivers and LED modules, the values shown for technical LED parameters, including performance parameters, are typical. Actual values of specific products in specific configurations may vary from these typical values. The information and diagrams contained in this document do not constitute an offer or contractual obligation. Product parameters may change as a result of technical innovation and will be undertaken without prior notice. Our manufacturing conforms to DIN-, EN-, and VDE-, CE regulations.