1,35 kWp Solar Bundle - EASY 1.3

Smart energy one-stop solution

This 1,35 kWp off-grid solar power system with battery is a sustainable, smart energy storage solution for improving household energy efficiency.

By integrating advanced storage features, the system enables homeowners to optimize their energy consumption, reduce dependence on the grid, and minimize energy costs. Our complete solution includes all necessary components such as an inverter, 2 kW battery, 3 solar modules with 450 Wp, a combiner box, and all required solar cables for the bundle.

Solar power systems with batteries offer households a reliable and environmentally friendly way to manage energy. For example, they weigh only 27 kg with a storage capacity of 2048 Wh.



Technical description:

Battery rated voltage:25,6VDCBattery capacity:2048 WhMPPT voltage range:30-100 VDCPV input voltage:30-108 VCDC

Max PV input power:1600 WCharge current range:0-60ARated output power:2000WMax AC input power:5000WAC input voltage:170-280VACOutput voltage:230VACOutput frequency50/60Hz auto

Cell technology: Lifepo4 Lithium iron phosphate

Cycle life: ≈ 6000 Cycles @ 80%

Work environment temperature: -20°C~50°C

Storage environment temperature: -20°C~60°C

Operating /Storage/humidity: ≤90%RH

Scalability: Max 4 Solar panels 450Wp

Solar panel typ:Monocrystalline silicon, max. 450 Wp

Color: Powerstation - white

Panel frame in natural aluminum

Main dimensions powerbox: H 520 x W 450mm x D 162 mm

Main dimensions solar panel:H 1762 x W 1134 x D30 mm

Weight powerbox: 27 kg

Weight each solar panel: 24,6 kg/per pcs. Installation powerbox: Floor standing

Installation solar panels: on our fastening systems for walls, roofs or floors

Mounting systems + fastening: will be charged separately.

Wiring: all solar cables included

IP Rating IP21

Mounting: will be charged separately

Due to the complexity of the numerous possible combinations of inverters, batteries, and solar panels, the specified technical parameters, including the performance parameters, are typical values. The actual values of specific products in specific configurations may differ from these typical values. The information and diagrams contained in this document do not constitute an offer or a contractual obligation. Product parameters are subject to change due to technical innovations and are subject to change without prior notice. We manufacture in accordance with DIN, EN, VDE, and CE regulations.

